FliteLine[™] Advanced Avionics



Lightweight, compact navigation & communication

Brochure





- Remote-mount, stackable transceivers
- Palm-size, color displays
- Combined NAV/COM display
- Mil-grade performance without mil-cost
- Interfaces with glass displays





FliteLine[™] Avionics

Superior performance, global applicability

Feature	Rockwell Collins Pro Line	FliteLine [™] CDM-451
Time-to-Station	Up to 120 minutes	Up to 8 hours 31 minutes (up to 511 minutes)
Environmental Qualification	DO-160D	DO-160E
Input Power	28 Volts DC	18 to 33 Volts DC
Audio Output	50 mW	Variable depending on configuration
Distance (Range & Accuracy)	300 nmi +/-0.17nmi	300 nmi +/-0.1 nmi
Receiver Sensitivity	-85 dBm	-92 dBm





Canyon FliteLine[™] CDM-451 Distance Measuring System



Canyon FliteLine[™] DFS-43A Distance Finding System

For further information please contact:

Canyon Aerospace Communications - USA 6400 Wilkinson Drive Prescott, AZ 86301 USA T: +1 928-708-1550 F: +1 928-541-7627

E: sales.prescott@cobham.com

©2015 Canyon AeroConnect. All right reserved information supplied by Canyon AeroConnect communication is believed to be accurate reliable. Canyon AeroConnect assumes no responsibility for any errors in this brochure Canyon reserved the right without notice, to make changes in product design or specifications. Company and /or product names referenced herein may be trademarks and are the property of their respective owners.

FliteLine[™] Advanced Avionics

A complete suite of next generation navigation and communication equipment from Canyon AeroConnect

FAA-and EASA-certified, ready to install in fixed -or rotary-wing aircraft

Compact, Lightweight Robust Displays

FliteLine panel-mount contriols install quickly and easily, with minimal wiring chages when replacing many older radio controllers. Featuring LCD dispalys, they're NVG-compatible.

- CCN-955 COM/NAV Display combines Com & Nav tuning in a single display for a 50% space reduction. It supports 2 x 5 tuning and ARINC 429 interface
- CVC-152 VHF COM Display features 8.33-25 kHz selectable tuning. and covers the 118.000-136.975 standard and 11.000- 151.975 extended frequency ranges.
- CVN-252 VHF NAV Display shows active and standby frequencies, along with radial and bearing information. It supports 2 x 5 tuning and ARINC 429 interface.
- CTR-352 ATC Transponder Display controls dual, remote transponders. Both controller and flight segment identifiers are indexed via display.
- ADF Control Display controls dual remote ADF receivers. The display menu includes ADFStation, anenna, bearing, and BFO information

COM/NAV 121.700

150.98

117.500

110.850

ON RAD BRG

M 25 Khz 8.33 Khz TS

0

N /

COM

123.50

121.40



ADF

782

TST ANT ADF

^{ACT} 1431

PWR

Technical Specifications

Vidth:	2.50 in. (63.5 mm)
leight:	3.15 in. (80.01 mm)
ength:	4.29 in. (108.97 mm) including connector
Veight:	0.77 lbs. (0.35 kg)
ltitude:	55,000 feet (16,764 m)
emperature:	–4°F to +158°F (–20°C to +55°C)
ower Consumption:	280 mA max.
ower Requirements:	(lighting) 5.0 Vac, 5.0 Vdc & 28 Vdc

NAV

ACT 110.55

116.00

TST



Remote-mount, Stackable Transceivers

FliteLine's unique Digital Signal Processing (DSP) design has resulted in a system with reduced weight and volume, plus enhanced performance and reliability. FliteLine digital (ARINC 429) and analog interfaces maximizeinstallation flexibility, providing the ideal communication solution for helicopters. businees and regional jets, transport aircraft, and military trainers.

- CVC-151 Com is an all-digital DSP VHF transceiver which can be configured with 8.33 or 25 kHz channelling and 118–137 MHz (118–152 MHz available as on option). This open ARINC 429 architecture supports FMS and RMS –555 radio management system interfaces. The CVC–152 control display completes the Com System.
- CVN–251 VHF NAV receiver combines VOR. ILS. localizer, glideslope and marker beacon in one, line-replaceable unit. The CVN-251 supports the total navigation requirements for MFD moving map displays and retains analog interface support for HSIs, CDIs and RMIs. To Complete the Nav system, include the CVN-252 control display.
- CDM-451 DME simultaneously scans three ground stations, has a 32-watt transmitter, and provides independent DME outputs for dual EHSI/EHADI displays with another for the FMS system.
- DFS-43A Automatic Direction Finder is an all-digital system designed to provide ADF navigation reception from non-directional beacons (NDB), locator outer markers (LOM). and commercial AM broadcast stations.







Technical Specifications

	CVC-151
Width	2.4 in. 60.96 mm
Height	4.0 in. 101.6 mm
Length	12.95 in. 328.93 mm
Weight	3.75 lbs. 1.7 kg
Altitude	55,000 feet 16.764 m
Temp.	–67° to +185°F –55° to +70°C
Power Req.	28 Vdc
Current Req.	Rx 0.5 A Tx 4.5 A
Frequency Range	118.00- 136.975 MHz or 118.000- 151.975 MHz

	0111 201
n	2.4 in. 60.96 mm
n	4.0 in. 101.6 mm
ım	12.95 in. 328.93 mm
	3.75 lbs. 1.7 kg
eet 1	55,000 feet 16.764 m
185°F 70°C	-67° to +185°F -55° to +70°C 28 Vdc
	0.8 A

CVN-251

CDM-451
2.4 in. 60.96 mm
4.0 in. 101.6 mm
12.95 in. 328.93 mm
3.6 lbs. 1.63 kg
55,000 feet 16.764 m
–67° to +185° –55° to +70°C
27.5 Vdc (+/-20%)
1.2 A max

DFS-43A

4.1 in. 104.14 mm 4.0 in. 101.6 mm 13.33 in. 338.58 mm 5.64 lbs 2.56 kg 55.000 feet 16.764 m -67° to +185°F -55° to +70°C 27.5 Vdc (+/-20%) 0.6 A

190.0–1860 kHz and 2181-2183 kHz (. 5 spacing)